



KRAMER

PT-120

Computer Graphics Video over Twisted Pair Receiver



The PT-120 is a twisted pair receiver for computer graphics video signals. It converts a twisted pair signal from a PT-110 transmitter (or other compatible Kramer transmitter) to a computer graphics signal

FEATURES

HDTV Compatible

Max. Resolution - WUXGA & 1080p

Level (Gain) & EQ (Peaking) Controls

System Range - Up to 100m (320ft). Greater distances possible depending on signal resolution and cable

Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) cable such as CAT 5

Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other

Ultra Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 twisted pair on an RJ-45 connector
OUTPUT:	1 VGA/UXGA on a 15-pin HD connector
MAX. OUTPUT LEVEL:	1.5Vpp
MAX. RESOLUTION:	WUXGA & 1080p
DIFF. GAIN:	2.9% (worst case)
DIFF. PHASE:	0.3Deg (worst case)
K-FACTOR:	<0.05%
S/N RATIO:	69dB (worst case)
CONTROLS:	-7.7dB to +3.1dB, 130m (level); 0dB to +25dB, (EQ.) @50MHz
COUPLING:	DC
POWER CONSUMPTION:	12V DC, 175mA
INCLUDED ACCESSORIES:	Power supply
OPTIONS:	RK-4PT 19" rack adapter

